

	<u>ENGLISH</u>	<u>SI</u>	
Performance			
Sensitivity(± 3 %)	2000 mV/g	203.9 mV/(m/s ²)	[6]
Measurement Range	± 2 g pk	± 19.6 m/s ² pk	
Frequency Range(± 3 dB)	0 to 200 Hz	0 to 200 Hz	[7]
Frequency Range(± 3 dB)	0 to 400 Hz	0 to 400 Hz	[2]
Phase Response(10 Hz)	<3.0 °	<3.0 °	
Broadband Resolution(0.5 to 100 Hz)	.1 mg rms	.001 m/s ² rms	[2]
Non-Linearity	≤ 1 %	≤ 1 %	[8]
Transverse Sensitivity	≤ 5 %	≤ 5 %	
Environmental			
Overload Limit(Shock)	± 2000 g pk	± 19,620 m/s ² pk	
Temperature Range(Operating)	-65 to 250 °F	-54 to 121 °C	
Temperature Range(Storage)	-65 to 250 °F	-54.0 to 121 °C	
Temperature Coefficient of Sensitivity	± 5 %	± 5 %	[4]
Zero g Offset Temperature Coefficient	± 4 % FSO	± 4 % FSO	[5][4]
Base Strain Sensitivity(Measured at 250 µε)	.0005 g	.0049 m/s ²	[2]
Electrical			
Excitation Voltage	6 to 30 VDC	6 to 30 VDC	
Current Consumption	≤ 10 mA	≤ 10 mA	
Output Impedance	≤ 120 Ohm	≤ 120 Ohm	
Offset Voltage(0 g)	± 320 mVDC	± 320 mVDC	[1]
Common Mode Voltage(± 0.1 VDC)	+2.5 VDC	+2.5 VDC	
Spectral Noise(1 to 100 Hz)	20 µg/√Hz	196 (µm/sec ²)/√Hz	[2]
Electrical Isolation(Case)	>10 ⁸ Ohm	>10 ⁸ Ohm	[3]
Physical			
Housing Material	Anodized Aluminum	Anodized Aluminum	
Sealing	Epoxy	Epoxy	
Size (Height x Length x Width)	0.30 in x 1.00 in x .85 in	7.5 mm x 25.4 mm x 21.6 mm	
Weight(without cable)	0.35 oz	9.92 gm	[2]
Electrical Connector	Integral Cable	Integral Cable	
Electrical Connection Position	Side	Side	
Cable Termination	Pigtail Ends	Pigtail Ends	
Cable Type	010 4-cond Shielded	010 4-cond Shielded	
Cable Length	10 ft	10 ft	
Mounting	Through Holes (2)	Through Holes (2)	

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:

[1] Offset tolerance is based on manufacturers supplied cable length.
 [2] Typical.
 [3] Case and shield to mounting surface or cable leads.
 [4] -65 to +250 °F, ref. 75 °F (-54 to +121 °C, ref. 24 °C)
 [5] FSO = Full Scale Output over the Measurement Range (8VDC).
 [6] Measured at 10 Hz, 1.0 pk
 [7] Minimum, verified with Calibration data.
 [8] Least-squares, straight line method, % FSO.
 [9] See PCB Declaration of Conformance PS025 for details.

SUPPLIED ACCESSORIES:
 Model 081A103 Mounting screw (2)
 Model ACS-145 Phase and Amplitude Calibration from 2 Hz to ±3 dB of frequency range (1)
 Model M081A103 Mounting screw and washer, M3 x 0.5 thread (2)

OPTIONAL ACCESSORIES:
 Model 080A208 Triaxial mounting block

Entered: LK	Engineer: JJD	Sales: WDC	Approved: NJF	Spec Number:
Date: 11/23/2016	Date: 11/23/2016	Date: 11/23/2016	Date: 11/23/2016	60418



*All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.*



Phone: 716-684-0001
Fax: 716-684-0987
E-Mail: info@pcb.com