


Model Number <b>682A16</b>	<b>UNIVERSAL TRANSMITTER W/ICP POWER</b>		Revision NR ECN #:		
<b>Environmental</b> Temperature Range (Operating) Humidity Range (Non-Condensing) <b>Electrical</b> Supply Voltage Current Consumption Excitation Voltage (delivered to sensor) Constant Current Excitation (delivered to sensor) <b>Physical</b> Size (Width x Height x Depth) Weight	<b>ENGLISH</b> -4 to 140 °F < to 95 % 19.2 to 300 VDC ≤2.5 W 23 to 25 VDC 3 to 5 mA 0.93 in x 4.29 in x 4.09 in 6.00 oz	<b>SI</b> -20 to 60 °C < to 95 % 19.2 to 300 VDC ≤2.5 W 23 to 25 VDC 3 to 5 mA 23.5 mm x 109 mm x 104 mm 170 gm	<b>Optional Versions</b> (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.)		
<p><i>All specifications are at room temperature unless otherwise specified.</i>          In the interest of constant product improvement, we reserve the right to change specifications without notice.</p>					
Entered: ECB Date: 03/12/2010		Engineer: NJF Date: 03/12/2010	Sales: MRS Date: 03/12/2010	Approved: NJF Date: 03/12/2010	Spec Number: <b>33025</b>
 <b>IMI SENSORS</b> A PCB PIEZOTRONICS DIV.		3425 Walden Avenue Depew, NY 14043 UNITED STATES Phone: 716-684-0003 Fax: 716-684-3823 E-mail: imi@pcb.com Web site: www.imi-sensors.com			