

Model Number 1203-11A		LOW PROFILE LOAD CELL			Revision: B ECN #: 43809	
Performance		ENGLISH	SI		OPTIONAL VERSIONS	
Measurement Range	500 lbf	2224 N	[6][7]	Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used. 1203-11B - PC04E-10-6P Connector 1203-11C - PT02E-12-8P Connector 1203-11D - PC01E-12-8P Connector		
Sensitivity(± 10 %)(RO)	2.0 mV/V	2.0 mV/V	[3][1]			
Non-Linearity	≤ 0.04 % FS	≤ 0.04 % FS	[6][8]			
Hysteresis	≤ 0.03 % FS	≤ 0.03 % FS	[6][8]			
Non-Repeatability	≤ 0.01 %RO	≤ 0.01 %RO	[3][8]			
Eccentric Load Sensitivity	0.25 %/in	0.25 %/25.4mm	[8]			
Resonant Frequency	2.35 kHz	2.35 kHz				
Side Load Sensitivity	0.25 %/in	0.25 %/25.4mm	[8]			
Creep(in 20 minutes)	0.025 %	0.025 %	[8]			
Static Error Band	≤ 0.04 % FS	≤ 0.04 % FS	[6][8]			
Environmental				NOTES: [1]Nominal. [2]Calibrated at 10 VDC, usable 5 to 20 VDC or VAC RMS. [3]RO - Rated Output. [4]Singularly applied, i.e. no other extraneous loads. [5]Over compensated operating temperature range. [6]FS - Full Scale. [7]Calibrated in tension and compression. [8]Performance specifications guaranteed with factory installed optional Tension Base 084A100 [9]See Outline Drawing 49605 for Complete Dimensions		
Overload Limit	750 lbf	3336 N				
Load Limit(Side Force, F _X or F _Y)	250 lbf	1112 N	[4]			
Load Limit(Bending Moment, M _X or M _Y)	250 lbf-in	28 Nm	[4]			
Load Limit(Axial Torque, M _Z)	250 lbf-in	28 Nm	[4]			
Temperature Range(Operating)	-65 to +200 °F	-54 to +93 °C				
Temperature Range(Compensated)	+15 to +115 °F	-9 to +46 °C				
Temperature Effect on Output(Maximum)	± 0.0008 %Reading/°F	± 0.0018 %Reading/°C	[5]			
Temperature Effect on Zero Balance(Maximum)	± 0.0008 %FS/°F	± 0.0018 %FS/°C	[5]			
Electrical						
Bridge Resistance	350 Ohm	350 Ohm	[1]			
Excitation Voltage(Recommended)	10 VDC	10 VDC	[2]			
Insulation Resistance	>5K GOhm	>5K GOhm				
Zero Balance	± 1 %RO	± 1 % FS	[3]			
Output Polarity	+Tension	+Tension				
Physical						
Size (Diameter x Height)	4.12 in x 2.50 in	104.6 mm x 63.5 mm	[9]			
Weight	6.4 lb	2.9 kg				
Mounting Thread	5/8 - 18 UNF-3B	No Metric Equivalent				
Housing Material	Painted Steel	Painted Steel				
Sensing Element	Strain Gage	Strain Gage				
Mounting Torque	200 lbf-in	23 Nm				
Deflection at Full Scale Capacity	0.001 in	0.025 mm				
Electrical Connector	PT02E-10-6P	PT02E-10-6P				
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.						
 PCB Load & Torque, Inc. 24350 Indoplex Circle Farmington Hills, MI 48335 UNITED STATES Phone: 866-684-7107 Fax: 716-684-0987 E-Mail: Itinfo@pcbloadtorque.com Web site: http://www.pcbloadtorque.com						