

	<u>ENGLISH</u>	<u>SI</u>	
Performance			
Measurement Range	10 klb	44 kN	[5]
Sensitivity(± 10 %)	3 mV/V	3 mV/V	[6]
Non-Linearity	≤ 0.05 % FS	≤ 0.05 % FS	
Hysteresis	≤ 0.05 % FS	≤ 0.05 % FS	
Non-Repeatability	≤ 0.02 %RO	≤ 0.02 %RO	
Resonant Frequency	10 kHz	10 kHz	
Environmental			
Overload Limit	15 klb	67 kN	
Load Limit(Side Force, F _X or F _Y)	5000 lb	22 kN	[3]
Load Limit(Bending Moment, M _X or M _Y)	5000 in-lb	565 N-m	[3]
Load Limit(Axial Torque, M _Z)	5000 in-lb	565 N-m	[3]
Temperature Range(Operating)	-65 to +200 °F	-54 to +93 °C	
Temperature Range(Compensated)	+70 to +170 °F	+21 to +76 °C	
Temperature Effect on Output(Maximum)	± 0.002 %Reading/°F	± 0.0036 %Reading/°C	[4]
Temperature Effect on Zero Balance(Maximum)	± 0.001 %FS/°F	± 0.0018 %FS/°C	[4]
Electrical			
Bridge Resistance	700 ohm	700 ohm	[1]
Excitation Voltage(Recommended)	10 VDC	10 VDC	[2]
Insulation Resistance	>5x10 ⁹ ohm	>5x10 ⁹ ohm	
Zero Balance	≤ 1 % FS	≤ 1 % FS	
Physical			
Size (Diameter x Height)	4.12 in x 1.37 in	104.6 mm x 34.8 mm	
Weight	2.88 lb	1.31 kg	
Mounting Thread	5/8 - 18 Female	No Metric Equivalent	
Deflection at Full Scale Capacity	0.0015 in	0.038 mm	
Sensing Element	Strain Gage	Strain Gage	
Housing Material	Painted Steel	Painted Steel	
Electrical Connector	PT02E-10-6P	PT02E-10-6P	
Electrical Connection Position	Side	Side	

*All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.*

ICP® is a registered trademark of PCB Group, Inc.

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:

[1] Nominal.
 [2] Calibrated at 10 VDC, usable 5 to 20 VDC or VAC RMS.
 [3] Singularly applied, i.e. no other extraneous loads.
 [4] Over compensated operating temperature range.
 [5] FS - Full Scale.
 [6] RO - Rated Output.

OPTIONAL ACCESSORIES:
 Model 084A100 TENSION LOAD BASE W/ 5/8-18 UNF-3B THD
 Model 181-012A PT06A-10-6S(SR)

Entered: <i>YMM</i>	Engineer: <i>ATB</i>	Sales: <i>gn</i>	Approved: <i>ATB</i>	Spec Number:
Date: <i>10/8/10</i>	Date: <i>10/8/10</i>	Date: <i>10/8/10</i>	Date: <i>10/8/10</i>	18361



PCB LOAD & TORQUE
A PCB GROUP COMPANY

PCB Load & Torque, Inc.
 24350 Indoplex Circle
 Farmington Hills, MI 48335
 UNITED STATES
 Phone: 866-684-7107
 Fax: 716-684-0987
 E-Mail: ltinfo@pcbloadtorque.com
 Web site: <http://www.pcbloadtorque.com>