

Model Number 3713F11200G	TRIAXIAL DC RESPONSE ACCELEROMETER				Revision: NR ECN #: 49223
Performance	ENGLISH	SI			OPTIONAL VERSIONS
Sensitivity(± 3 %)	6.75 mV/g	0.69 mV/(m/s ²)	[5]		Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
Measurement Range	± 200 g pk	± 1962.0 m/s ² pk			
Frequency Range(± 5 %)	0 to 1500 Hz	0 to 1500 Hz			
Frequency Range(± 10 %)	0 to 2500 Hz	0 to 2500 Hz			
Resonant Frequency	11.8 kHz	11.8 kHz	[2]		
Phase Response(100 Hz)	<10 °	<10 °			
Non-Linearity	≤ 1 %	≤ 1 %	[6]		
Broadband Resolution(0.5 to 100 Hz)	6 mg rms	0.6 m/s ² rms	[2]		
Transverse Sensitivity	≤ 3 %	≤ 3 %			
Environmental					NOTES:
Overload Limit(Shock)	± 3000 g pk	± 29,420 m/s ² pk			[1] Offset tolerance is based on 10 ft of 037 test cable.
Temperature Range(Operating)	-65 to +250 °F	-54.0 to +121 °C			[2] Typical.
Temperature Range(Storage)	-65 to +250 °F	-54.0 to +121 °C			[3] -65 to +250 °F, ref. 75 °F (-54 to +121 °C, ref. 24 °C)
Temperature Coefficient of Sensitivity	± 2.5 %	± 2.5 %	[3]		[4] FSO= Full Scale Output over the Measurement Range
Zero g Offset Temperature Coefficient	± 1.5 % FSO	± 1.5 % FSO	[3][4]		[5] Measured at 100 Hz, 10 grms.
Base Strain Sensitivity	0.001 g/με	0.01 (m/s ²)/με	[2]		[6] Zero-based, least-squares, straight line method.
Magnetic Sensitivity	40 μg/gauss	3.9 (m/s ²)/Tesla	[2]		[7] See PCB Declaration of Conformance PS027 for details.
Electrical					
Excitation Voltage	5 to 32 VDC	5 to 32 VDC			
Current Consumption	≤ 15 mA	≤ 15 mA			SUPPLIED ACCESSORIES: Model 080A12 Adhesive Mounting Base (1) Model 081B05 Mounting Stud (10-32 to 10-32) (1) Model ACS-172T Triaxial Phase and Amplitude Calibration from 5 Hz to +5% frequency range Model M081B05 Mounting Stud 10-32 to M6 X 0.75 (1)
Output Impedance	≤ 120 Ohm	≤ 120 Ohm			
Offset Voltage(0 g)	± 20 mVDC	± 20 mVDC	[1]		
Spectral Noise	800 μg/√Hz	7848 (μm/sec ²)/√Hz	[2]		
Electrical Isolation(Case)	>10 ⁸ Ohm	>10 ⁸ Ohm			
Physical					
Housing Material	Titanium	Titanium			
Sealing	Hermetic	Hermetic			
Size (Length x Width x Height)	0.8 in x 0.8 in x 0.8 in	20.3 mm x 20.3 mm x 20.3 mm			
Weight	0.6 oz	17.3 gm			
Electrical Connector	9-Pin	9-Pin			
Electrical Connection Position	Side	Side			
Mounting Thread	10-32 Female	10-32 Female			
 All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice. This model, designated with an RH prefix, is RoHS compliant. For further details, and to obtain PCB's RoHS Statement of Conformance, please visit http://www.pcb.com					
				Entered: LK	Engineer: NJF
				Sales: WDC	Approved: BAM
				Spec Number:	
				Date: 3/15/2019	Date: 3/15/2019
				Date: 3/15/2019	Date: 3/15/2019
				70528	
					
				3425 Walden Avenue, Depew, NY 14043	
				Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com	